



# DeepCool PF650 power supply unit 650 W 20+4 pin ATX ATX Black

**Brand :** DeepCool **Product code:** R-PF650D-HA0B-EU

**Product name :** PF650

- OPP/OVP/SCP
  - 80 PLUS White
  - 650 W
- 650 W, ATX 12V V2.4, 80 PLUS White, 120 mm Hypro Bearing, 150×140×86 mm, black

## DeepCool PF650 power supply unit 650 W 20+4 pin ATX ATX Black:

The DeepCool PF Series Power Supply Unit offers safe and stable power performance with reliable 80 PLUS Standard efficiency and affordable pricing.

### TO HIGHER STANDARDS


Certified for 80 PLUS 230V EU Standard efficiency that ensures 85% efficiency under typical loading of 50%. Better efficiency translates into lower energy waste and lower temperatures for more cost savings.

### SILENT HYDRAULIC BEARING FAN

Optimally balanced for low-noise performance, the 120mm fluid bearing fan improves overall life expectancy and reduces friction and vibration.

### FLAT BLACK CABLES

Stealthy and flexible, the fixed flat black cables are easy to maneuver for cable management while also taking up less space in your system.



| Power                                         |                                         | Performance                           |                        |
|-----------------------------------------------|-----------------------------------------|---------------------------------------|------------------------|
| Total power *                                 | 650 W                                   | 80 PLUS certification *               | 80 PLUS White          |
| AC input voltage *                            | 230 V                                   | Purpose *                             | PC                     |
| Efficiency                                    | 85%                                     | Power supply unit (PSU) form factor * | ATX                    |
| Power protection features                     | Over power, Over voltage, Short circuit | Bearing technology                    | Hypro Bearing          |
| Ports & interfaces                            |                                         | Mean time between failures (MTBF)     | 100000 h               |
| Motherboard power connector *                 | 20+4 pin ATX                            | Design                                |                        |
| Motherboard power cable length                | 55 cm                                   | Product colour                        | Black                  |
| Number of SATA power connectors               | 6                                       | Cooling type                          | Active                 |
| SATA power cable length                       | 450 mm                                  | Fan diameter                          | 12 cm                  |
| Peripheral (Molex) power connectors (4-pin) * | 2                                       | Number of fans                        | 1 fan(s)               |
| Peripheral (Molex) power cable length         | 900 mm                                  | Operational conditions                |                        |
| EPS power connector (4+4 pin)                 | ✓                                       | Operating temperature (T-T)           | 0 - 40 °C              |
| ATX power connector (20+4 pin)                | ✓                                       | Certificates                          |                        |
| Cabling type                                  | Non-Modular                             | Certification                         | CB/CCC/CE/UKCA/EAC/RCM |
|                                               |                                         | Weight & dimensions                   |                        |
|                                               |                                         | Width                                 | 150 mm                 |
|                                               |                                         | Depth                                 | 140 mm                 |
|                                               |                                         | Height                                | 86 mm                  |



6933412711469

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 02-MAY-2026. Prints or copies of Information are only valid on the printed Publication date